

**AMENDMENTS TO THE CLAIMS:**

**Claims 1-10 (cancelled).**

11. (Previously Presented) An ophthalmologic device comprising:
- a controllable illumination unit;
  - an observation system;
  - an image recording unit;
  - a central control unit;
  - an output unit;
  - an eye tracker unit; and
  - means for relative positioning of the ophthalmologic device with respect to the eye to be examined; and
- wherein the eye tracker unit includes an imaging system, said imaging system having at least two different adjustable magnifications.
12. (Previously Presented) The ophthalmologic device comprising a controllable illumination unit, an observation system, an image recording unit, a central control unit, an output unit, an eye tracker unit, and means for relative positioning of the ophthalmologic device with respect to the eye to be examined, wherein the observation system is a stereo microscope with changeable magnification.

Serial No.: 10/533,394

13. (Previously Presented) The ophthalmologic device according to claim 11, wherein the imaging system of the eye tracker unit is a zoom objective or an interchangeable objective.

14. (Currently Amended) The ophthalmologic device according to claim 11, wherein the image recording unit is a digital high-resolution camera with a ~~high~~ image rate which can have a tilting device for tilting ~~the~~ a camera chip relative to the optical axis for Scheimpflug correction and/or is capable of recording and storing image sequences.

15. (Currently Amended) The ophthalmologic device according to claim 11, wherein the ~~optical~~ image recording unit operates synchronous with the image rate of the digitally controllable illumination unit.

16. (Currently Amended) The ophthalmologic device according to claim 11, wherein the central control unit has a user interface with conventional input devices ~~such as keyboard, mouse, trackball, joystick, or the like,~~ and/or has different ~~control~~ controlling ~~modes~~ and evaluating modes.

17. (Previously Presented) The ophthalmologic device according to claim 11, wherein the output unit is a monitor and/or printer.

18. (Currently Amended) A method for positioning an ophthalmologic device, comprising the steps of:

bringing the patient's eye to a fixed position by an existing chin rest and forehead support;

selecting a wide-angle setting of ~~the~~ an imaging system of ~~the~~ an eye tracker unit;

Serial No.: 10/533,394

said eye tracker unit with said wide-angle setting of the imaging system supplying signals containing the coordinates of the eye relative to the eye tracker unit and, therefore, also relative to the optical axis of the ophthalmologic device ~~itself~~;

said eye tracker unit generating a corresponding reference value from these signals with respect to amount of movement and direction for ~~the~~ a positioning device;

said eye tracker unit also supplying ~~this~~ a reference signal to the positioning device;

carrying out ~~the~~ an alignment by continuous detection of the eye position and relative movement; and

changing the magnification of the imaging system of the eye tracker unit after alignment in x-direction and y-direction.

19. (Currently Amended) A method for positioning an ophthalmologic device, comprising the steps of:

bringing the patient's eye to a fixed position by an existing chin rest and forehead support;

selecting a wide-angle setting of an objective of ~~the~~ a stereo microscope of ~~the~~ an image recording unit;

said image recording unit supplying signals containing the coordinates of the eye relative to the image recording unit and, therefore, also relative to the optical axis of the ophthalmologic device ~~itself~~;

said image recording unit generating a corresponding reference value from these signals with respect to amount of movement and direction for ~~the~~ a positioning device; and

Serial No.: 10/533,394

said image recording unit also supplying ~~this~~ a reference signal to the positioning device;

carrying out ~~the~~ an alignment by continuous detection of the eye position and relative movement; and

changing the objective setting of the stereo microscope after alignment in x-direction and y-direction.

20. (Currently Amended) The method for positioning an ophthalmologic device according to claim 18, wherein an alignment of the ophthalmologic device in z-direction is carried out after alignment has been carried out in x-direction and y-direction and after ~~the~~ an aperture angle of the imaging system of the eye tracker unit has been changed.

21. (Currently Amended) The method for positioning an ophthalmologic device according to claim 18, wherein ~~the~~ detection of the eye by the eye tracker unit is carried out in such a way that in evaluating the image of the eye generated by illumination the pupil center is exactly determined and ~~the~~ tracking of the light marks is carried out by continuous detection of the pupil by the eye tracker unit.

22. (Cancelled)